

SCSI Device Check List (Sampler MPC)

April 25, 2000

Media	Maker	Model	Firmware Version	S1000 V4.4	S1100 V4.3	S3000 V2.0	S2000/XL V2.0	MPC3000 V3.11	MPC2000 V1.72	MPC2000XL V1.11	S5/S6000 V1.30	Note	CHECK DATE
CD-ROM X32	TEAC	CD-532S	1.0A	NG	NG	OK	OK	OK	OK	OK	OK	A Hard Disk read Error message may appear when try to access it during the CD-ROM sleep mode, but it is no problem with trying "Access" many times.	99.3.
CD-ROM X40	PLEXTOR	PX-40TS	1.00	NG	NG	OK	OK	OK*	NG	OK	OK	*Should be set to ID 5 and "Make Active"	99.6.
CD-ROM X35	PIONEER	DR-766	1.00	NG	NG	OK	OK	OK	OK		OK		99.3.
CD-RW X20	PLEXTOR	PX-W8220Te	1.01							OK	OK	Only for CD-ROM , can not be used as CD-R (Rewrite)	99.8
CD-RW X20	PLEXTOR	PX-W4220Te	1.01	OK		OK	OK	OK	OK			Only for CD-ROM , can not be used as CD-R (Rewrite)	99.3
CD-RW X12	RICOH	MP6200S	2.20	NG	NG	OK	OK	OK	OK			Only for CD-ROM , can not be used as CD-R (Rewrite)	99.3
CD-RW X24	RICOH	RW7060S	1.70	NG	NG	NG	NG	NG	NG	OK	OK	Only for CD-ROM , can not be used as CD-R (Rewrite)	00.4
CD-RW X32	MELCO	CDRW-S8432	2.21	NG	NG	NG	NG	NG	NG	OK	OK	Only for CD-ROM , can not be used as CD-R (Rewrite)	
2.5inch HD 540MB	TOSHIBA	MK1924FBV		NG	NG	NG	OK	NG	NG			Internal for S3000XL,CD3000XL,and S3200XL with KIT-SHD524	97.2.
3.5inch HD 4.5GB	Seagate	Medalist pro ST34520N	1281								OK	OK for Internal drive in S5000/6000	99.2
3.5inch HD 4.5GB	IBM	DDRS-34560U	S97B							OK	OK	OK for Internal drive in S5000/6000	99.6.
ZIP100	IOMEGA FujiFilm	ZIP 100	H.14	OK	OK	OK	OK	OK	OK	OK	OK	Can not use "Write Protect"	97.10.
ZIP250	IOMEGA	ZIP 250	H.41			OK	OK	OK	OK	OK	OK		99.9
JAZ 1GB	IOMEGA	jaz 1GB	H.71	NG	OK*	OK*	OK*	NG		OK	OK	*A "SCSI NOT READY" message may appear during Auto Sleep mode	97.11.
3.5inch MO 230MB	FUJITSU	M2512EL	0010			OK*	OK*	OK	OK	OK	OK*	*may have noise on D-D Recording (save/load is OK)	97.10
3.5inch MO 230MB	FUJITSU	MCE3023SS	0030		NG	OK*	OK*	OK	OK	OK	OK*	*may have noise on D-D Recording (save/load is OK)	99.10
3.5inch MO 230MB	OLYMPUS	MOS332	2.5	OK*	OK*	OK*	OK*	OK	OK			*Use only "ARR" during the format process *Use pre-formatted disks.	
3.5inch MO 640MB	KONICA	OMD-9060	1.05				NG*				OK	*may have noise on D-D Recording (save/load is OK)	
3.5inch MO 640MB	FUJITSU	MCE3064SS	0030		NG	OK*	OK*	OK*	OK*	OK*	OK	* Can't use 640MB Disk due to 2048 sector	99.10.
3.5inch MO 1.3GB	FUJITSU	MCD3130SS	0010				OK*			OK*	OK	* Can't use 640MB Disk due to 2048 sector	99.10

OK: can be used

OK*: can be used with some condition (refer to Note)

NG: can not be used

Space: not tested

S3000 series includes S2800, S3000,and S3200

S3000XL series includes S2000, S3000XL, S3200XL, and CD3000XL

Note: This check list is made with the basically test such as Format, Save, Load, and some DD-recording on Akai EMI service.

It may not be used if the drive or Akai product are changed the firmware or OS software version.